

Click the hot spots to find out more



In gastronomy, baking, and kitchen hygiene appliances, steam is a key component generated using a piped mains water supply. The problem is that different water conditions, such as hard water or corrosive water, need specific filters.

The PROGUARD Gastronomy is a universal professional water filtration solution, with a high volume electric reverse osmosis (RO) filter system and 5μ m particle retention carbon block pre-filter to reduce sediments and ≥ 97 % of salts in the steamed water. The high-performance system with a powerful flow rate fulfills all conditions and needs of professional kitchens. It is a premium line of defence against limescale, gypsum, and potentially corrosive substances caused by high levels of chlorides and sulfates and it operates successfully with all types of incoming drinking water.







Combi Steamer

With this high-performing filter solution, your machines are shielded from limescale, gypsum, and corrosion.





Baking Oven

The long filter life of PROGUARD Gastronomy yields a full year of seamless service for constantly perfect baking results.





Dishwasher

The high-performance, dual membrane RO system for total demineralization, results in spotless utensils, glasses, and crockery.











BRITA

Click the hot spots to find out more







BRITA PROGUARD Gastronomy problem solving



Problem

Different water conditions cause different issues within combi steamers, ovens and dishwashers.

Therefore different water filters are needed.





Problem

Professional kitchens have fluctuating water demands, from low demands with peaks to constantly high demands.







Problem



BRITA

Click the hot spots to find out more









Different water conditions cause different issues within combi steamers, ovens and dishwashers.

Therefore different water filters are needed.

Solution

PROGUARD Gastronomy is the professional one fits all solution that reduces the risk of machine scaling, gypsum deposits and corrosion as it is able to handle all incoming waters*.

*Only drinking water quality may be used





Problem

Professional kitchens have fluctuating water demands, from low demands with peaks to constantly high demands.




Problem



BRITA

Click the hot spots to find out more



Product benefit

- Reliable protection from corrosion, limescale and gypsum deposits due to 2 Premium RO-membrane with a salt retention rate of \geq 97%
- Bypass adjustment to blend with raw water, if boiler ovens require a desired level of mineralization
- Carbon block pre-filter with 5µm particle retention to ensure smooth operation and a fresh taste







BRITA PROGUARD Gastronomy problem solving



Problem

Different water conditions cause different issues within combi steamers, ovens and dishwashers. Therefore different water filters are needed.





Problem

Professional kitchens have fluctuating water demands, from low demands with peaks to constantly high demands.







Problem



BRITA

Click the hot spots to find out more







Problem

Different water conditions cause different issues within combi steamers, ovens and dishwashers.

Therefore different water filters are needed.



Problem

Professional kitchens have fluctuating water demands, from low demands with peaks to constantly high demands.

Solution

PROGUARD Gastronomy is a high-performance system with a powerful flow rate to fulfill all conditions and needs of professional kitchens.






Problem



BRITA

Click the hot spots to find out more



Product benefit

- High performing RO system with 200 l/h at 25°C / 140 l/h at 15°C
- Electrical RO system with rotary valve pump for easy handling & operation
- Very compact RO system to fit under each counter
- Water conversion factor up to 50%





BRITA PROGUARD Gastronomy problem solving



Problem

Different water conditions cause different issues within combi steamers, ovens and dishwashers.

Therefore different water filters are needed.





Problem

Professional kitchens have fluctuating water demands, from low demands with peaks to constantly high demands.







Problem



BRITA

Click the hot spots to find out more







Problem

Different water conditions cause different issues within combi steamers, ovens and dishwashers.

Therefore different water filters are needed.



Problem

Professional kitchens have fluctuating water demands, from low demands with peaks to constantly high demands.





Problem

Lack of transparency makes it hard to monitor the filtration and schedule maintenance.


Solution

PROGUARD Gastronomy is equipped with an easy to use display, showing all the relevant performance data at a glance.



BRITA

Click the hot spots to find out more



Product benefit

Colored display shows all relevant parameter:

- Lifetime in days
- Pressure in bar (IN, OUT)
- Flow rate in I/h
- Conductivity in μS/cm





BRITA PROGUARD Gastronomy problem solving



Problem

Different water conditions cause different issues within combi steamers, ovens and dishwashers.

Therefore different water filters are needed.





Problem

Professional kitchens have fluctuating water demands, from low demands with peaks to constantly high demands.






Problem








1 Pre-filtration

Carbon block filtration, through a pre-filter cartridge outside the housing, retains coarse particles down to 5 μ m and protects the two premium reverse osmosis membranes. In addition, the activated carbon filters out taste and odour impairing substances such as chlorine from the source.






1 Pre-filtration

Carbon block filtration, through a pre-filter cartridge outside the housing, retains coarse particles down to 5 μ m and protects the two premium reverse osmosis membranes. In addition, the activated carbon filters out taste and odour impairing substances such as chlorine from the source.

(2) RO membrane

Two premium reverse osmosis (RO) membranes remove ions and molecules, such as salts. With a salt retention rate of \geq 97 %, this stage reliably safeguards against corrosion, even in challenging water conditions. Moreover, RO helps prevent scale, gypsum and other contaminants from entering the machines. Working in combination with the mineralization adjustment, the resulting filtrate is impeccably clean as well as pH-neutral.





1 Pre-filtration

Carbon block filtration, through a pre-filter cartridge outside the housing, retains coarse particles down to 5 μ m and protects the two premium reverse osmosis membranes. In addition, the activated carbon filters out taste and odour impairing substances such as chlorine from the source.


2 RO membrane

Two premium reverse osmosis (RO) membranes remove ions and molecules, such as salts. With a salt retention rate of \geq 97 %, this stage reliably safeguards against corrosion, even in challenging water conditions. Moreover, RO helps prevent scale, gypsum and other contaminants from entering the machines. Working in combination with the mineralization adjustment, the resulting filtrate is impeccably clean as well as pH-neutral.

3 Bypass

The valve bypass adjustment provides machine-based mineralization levels configurable through the blending of raw water. This is especially important for boiler ovens requiring a specific level of mineralization stipulated in manufacturer's individual specifications.





1 Pre-filtration

Carbon block filtration, through a pre-filter cartridge outside the housing, retains coarse particles down to 5 μ m and protects the two premium reverse osmosis membranes. In addition, the activated carbon filters out taste and odour impairing substances such as chlorine from the source.

2 RO membrane

Two premium reverse osmosis (RO) membranes remove ions and molecules, such as salts. With a salt retention rate of \geq 97 %, this stage reliably safeguards against corrosion, even in challenging water conditions. Moreover, RO helps prevent scale, gypsum and other contaminants from entering the machines. Working in combination with the mineralization adjustment, the resulting filtrate is impeccably clean as well as pH-neutral.


3 Bypass

The valve bypass adjustment provides machine-based mineralization levels configurable through the blending of raw water. This is especially important for boiler ovens requiring a specific level of mineralization stipulated in manufacturer's individual specifications.

4 Display

The built-in display shows all relevant parameters such as pressure, flow rate and conductivity of the filtrate for intuitive system monitoring.





1 Pre-filtration

Carbon block filtration, through a pre-filter cartridge outside the housing, retains coarse particles down to 5 μ m and protects the two premium reverse osmosis membranes. In addition, the activated carbon filters out taste and odour impairing substances such as chlorine from the source.

2 RO membrane

Two premium reverse osmosis (RO) membranes remove ions and molecules, such as salts. With a salt retention rate of \geq 97 %, this stage reliably safeguards against corrosion, even in challenging water conditions. Moreover, RO helps prevent scale, gypsum and other contaminants from entering the machines. Working in combination with the mineralization adjustment, the resulting filtrate is impeccably clean as well as pH-neutral.

3 Bypass

The valve bypass adjustment provides machine-based mineralization levels configurable through the blending of raw water. This is especially important for boiler ovens requiring a specific level of mineralization stipulated in manufacturer's individual specifications.

4 Display

The built-in display shows all relevant parameters such as pressure, flow rate and conductivity of the filtrate for intuitive system monitoring.

(5) Pump

An electrical RO system with rotary valve pump ensures high performance, easy handling, and essential reliability.